



2-6278875-2 Product Details



2-6278875-2

TE Internal Number: 2-6278875-2



Fiber Optic Cable Assemblies



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Patch Cord
- Cable Assembly
- MT-RJ (No Pins) Fiber Optic Cable Connector Type, MT-RJ SECURE (No Pins) Fiber Optic Cable Connector Type
- Fiber Type = OM2 50/125 Micron
- Cable Assembly Type = MT-RJ SECURE (No Pins) to MT-RJ (No Pins)

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)



[Request Sample](#)



[Find Similar Products](#)



[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [CABLE ASSY, FIBER OPTIC, 50/125um, OFNP, MT-RJ GREE...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Feedback

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Designation](#) = Patch Cord
- Product Type = Cable Assembly
- Fiber Optic Cable Connector Type = MT-RJ (No Pins), MT-RJ SECURE (No Pins)
- Cable Assembly Type = MT-RJ SECURE (No Pins) to MT-RJ (No Pins)
- Cable Type = Twin Zip

Electrical Characteristics:

- Insertion Loss (dB) = 0.50
- Return Loss (dB) = 20

Termination Features:

- [Fiber Type \(Micron\)](#) = OM2 50/125

Dimensions:

- Cable Diameter (mm [in]) = 1.80 [.071]
- Length (M [ft]) = 22.00 [72.17]

Body Features:

- Cable Color = Orange
- Connector Color = Green
- Boot Body Style - Left = Standard
- Boot Color - Left = Beige
- Boot Body Style - Right = Standard
- Boot Color - Right = Beige
- Ferrule Material = Ceramic

Contact Features:

- Fibre Channel = No

Housing Features:

- Fiber Path Configuration = Pair Flipped

Configuration Features:

- [Mode](#) = Multimode
- Number of Fibers = 2
- [Cable Buffering](#) = Tight Buffered
- Connector(s) Exit Angle to Connector(s) Exit Angle = 180° to 180°

Industry Standards:

- [Flammability Rating Type](#) = OFNR (Riser) Jacket
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Product Availability:

- Region = Asia, North America, Latin America

Other:

- Brand = TE Connectivity

Corporate Information

- About TE
- Investors
- News Room
- Supplier Portal
- Careers
- Terms & Conditions
- Privacy Policy
- AODA Accessibility Policy
- AODA Multi-Year Accessibility Plan

Quick Links

- Distributor Inventory
- Product Cross Reference
- Documents & Drawings
- Product Compliance Support Center
- Site Map

Customer Support

- Email or Chat With Us
- Find a Phone Number
- Knowledge Base
- Manage Your Account

Keep Me Informed

